



### 型号/ Model: ZP

特征:应用于大小数据机房服务器机柜

#### ZP系列机柜标准配置 Cabinet Package Contents:

- |           |                           |          |                    |
|-----------|---------------------------|----------|--------------------|
| ● 框架1个    | Cabinet Frame 1pc         | ● 底板1个   | Bottom Panel 1pc   |
| ● 顶板1个    | Top Cover 1pc             | ● 理线板2根  | Cable Manager 2pcs |
| ● 前网门1个   | Front Mesh Door 1pc       | ● 脚轮4只   | Castor 4pcs        |
| ● 后双开网门1套 | Back Split Mesh door 1set | ● 平衡地脚4只 | Leveling Feet 4pcs |
| ● 侧板4块    | Side Panel 4pcs           |          |                    |

### 规格参数Specification

| 订购代码      | 容量       | 尺寸              | 整装体积                   |
|-----------|----------|-----------------|------------------------|
| Model No. | Capacity | Dimension       | Assembled packing(CBM) |
| ZP-6042   | 42U      | 600x1000x2000mm | 1.4                    |
| ZP-6142   |          | 600x1100x2000mm | 1.55                   |
| ZP-6242   |          | 600x1200x2000mm | 1.7                    |
| ZP-8042   |          | 800x1000x2000mm | 1.83                   |
| ZP-8142   |          | 800x1100x2000mm | 2                      |
| ZP-8242   |          | 800x1200x2000mm | 2.2                    |
| ZP-6247   | 47U      | 600x1000x2200mm | 1.55                   |
| ZP-6147   |          | 600x1100x2200mm | 1.7                    |
| ZP-6247   |          | 600x1200x2200mm | 1.83                   |
| ZP-8047   |          | 800x1000x2200mm | 2                      |
| ZP-8147   |          | 800x1100x2200mm | 2.2                    |
| ZP-8247   |          | 800x1200x2200mm | 2.4                    |

- 机柜标准: 符合GB/T3047.2-92标准, 兼容19"国际标准、公制标准和ETSI标准。
  - 机柜材质: 主体框架为G型材, 全部采用SPCC优质冷轧钢板制做。
  - 材料厚度: 立梁(方孔条): 2.0mm, 框架、横梁: 1.5mm, 其他: 1.2mm。
  - 承重: 额定静载 ≤ 2500Kg。
  - 防护等级: Ip20。
  - 柜门通风率: ≥ 75%。
  - 表面处理: 脱脂、水洗、陶化、水洗、静电喷涂。
  - 颜色: RAL9004(黑色), RAL7035(灰白)。
- Standard: Comply with the standard of GB/T3047.2-92 Compatible with 19 inch international standard, metric and ETSI standard.
  - Material: Main frame is made of G profile, others are made of SPCC Cold rolled steel.
  - Material thickness: Mounting profile: 2.0mm, frame, mounting rails: 1.5mm, mothers: 1.2mm.
  - Loading Capacity: 2500kgs.
  - Protection grade: IP20.
  - Ventilation Rate of Cabinet doors: ≥ 75%.
  - Surface Finish: Degreasing, washing, ceramics, washing, electrostatic spraying.
  - Color: RAL9004(Black), RAL7035(grey white)